



Section 1. Chemical Product and Company Identification

Product name Acculam® Epoxyglas	Trade Name NEMA Grades G10, G11, FR4, FR 5
Product Description	
Rigid composites having a glass fabric reinforcement with	ith an epoxy resin binder
Manufacturer	IN CASE OF EMERGENCY:
Accurate Plastics, Inc.	
18 Morris Place	Tel: 914-476-0700
Yonkers, NY 10705-1929	
,	Chemtrec:
Date of Preparation: 4/22/2015	Replaces: 12/14/13
Preparers Name KJ Soltys	

Section 2. Hazards Identification

As received this product is not classified as hazardous by OSHA. Dust and fumes generated during machining and processing of this product are classified as hazardous according to OSHA standards.

GHS Classification of Epoxyglas at Ambient Conditions		
Inhalation	Not Classified	
Skin	Not Classified	
Eyes	Not Classified	
Ingestion	Not Classified	
Cancer	Not Classified	
Chronic	Not Classified	

GHS Classification of Epoxy Fiberglass Laminate Dust and Fumes





WARNING!

Hazard Statements	
Dust generated during machining and grinding operations may cause eye	Н 315; Н332
irritation	
Fumes from thermal decomposition or burning may irritate eyes, nose &	H 315; H 320; H332; H 335
respiratory system	
Dust generated by machining operations can be explosive. Dust may	H 201 Mass explosion hazard
accumulate to explosive concentrations in uncontrolled environments.	

Precautionary Statements	
Avoid eye exposure to dust and fumes	P262
Avoid skin contact with dust and fumes	P 261
In case of inadequate ventilation wear respiratory protection	P 285

Section 3. Composition, Information on Ingredients

Component Information			
Chemical Name CAS #			
Fiberglass	65997-17-3		
Epoxy Resin	25036-25-3		

Section 4. First Aid Measures

Eyes	Immediately wash the eyes with large amounts of water for at least 15 minutes, occasionally lifting the lower and upper lids. Get medical attention immediately. Contact lenses should not be worn when working with this material.
Skin	Immediately wash the contaminated skin with soap and water. If redness, itching or a burning sensation develops, get medical attention.
Inhalation	Immediately move the exposed person to fresh air. If not breathing give artificial respiration and get immediate medical attention.
Ingestion	If large quantities of dust of particles have been swallowed, DO NOT INDUCE VOMITING. Treat symptoms. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flash Point	N/D		
Flammability Classification OSHA/NFPA	Flash Pt. <00°F Class: Solid		
Extinguishing Media	Carbon dioxide, water, foam.		
	Isolate fire area and deny unnecessary entry.		
	Fire fighters should wear positive-pressure self-contained breathing apparatus		
	(SCBA) and protective clothing.		
Unusual Fire and Explosions Hazards	Dust from machining and fabrication operations may be explosive if mixed		
_	with air in critical proportions in the presence of an ignition source.		
	Heat from fire can generate decomposition products that may cause a health		
	hazard.		

Section 6. Accidental Release Measures

Small Spills	Contain and manage dust during manufacturing. If collected dust is spilled from collection container sweep up spilled material using water spray to suppress the dust. Shovel into suitable disposal container. Eliminate all ignition sources.
Large Spills	Eliminate all ignition sources. Sweep up spilled material using water spray to suppress dust. Transfer to proper containers for disposal. Persons not wearing protective equipment should be excluded from the area of spill until cleanup has been completed.

Section 7. Handling & Storage

Store material in a clean, cool, ventilated area away from all sources of ignition. Dust generated during normal manufacturing operations can represent both a health hazard and a fire hazard. Use dust control equipment at the point of generation in machining and grinding operations. Wash hands and other exposed areas thoroughly after handling and wash soiled clothing before reuse.

Section 8. Exposure Controls/Personal Exposure

Component Information		Exposure Limits		
Chemical Name	C	4S #	TLV, TWA ACGIH	OSHA PEL, TWA
Fiberglass	6599	7-17-3	10 mg/m ³ (dust)	15 mg/m³ (total dust) 5 mg/m³ (respirable)
Epoxy Resin	2503	6-25-3	10 mg/m ³ (dust)	10 mg/m ³ (dust)
Grinding, cutting, or drilling epoxy fiber glass plastic produces nonrespirable fiber shaped plastic (organic) dust and resp fibrous glass dust regulated by OSHA as noted above. Respirable fiberglass dust may cause cancer.				
Eye Protection Minimize dust generating activities. Wear safety goggles with face shield. Contact lenses must not be worn.		7 0 00		
Wear gloves to protect against sharp edges and thermal effects wheated material. To prevent repeated or prolonged skin contact, with impervious clothing and boots.				
Respiratory Protection		If personal exposure cannot be controlled below applicable limits (See Section 2) by area ventilation, wear a properly fitted particulate respirator approved by NIOSH/MSHA for protection against dust.		y fitted particulate respirator
Ventilation		General area ventilation is acceptable if the exposure is maintained below applicable exposure limits. (See Section 8) Use local exhaust for sawing and machining operations.		
Ulther Precalitions		e wash fountains and safety sho	owers should be available in the	

Section 9. Physical and Chemical Properties

% Volatile Content by Weight	<0.05%	Specific Gravity (gm/cc)	1.6
Melting Point	N/A	Freezing Point (^o C)	N/A
Vapor Pressure (mm Hg)	N/A	Solubility in Water	Insoluble
Vapor Density (Air=1)	N/A	Appearance and Odor	Gray, Odorless Solid

Section 10. Stability and Reactivity

	V		
Stability	Stable		
Conditions to Avoid	Protect from heat, sparks, flame and possible sources of ignition.		
Incompatibility	Avoid contact with strong acids and bases.		
Hazardous Decomposition Products	Carbon dioxide, carbon monoxide, bromine and other hazardous gases. These gases and other volatiles may be generated under normal processing conditions.		
Hazardous Polymerization	Will Not Occur!		

Section 11. Toxicological Information (see Section 3. for Exposure Symptoms)

Acute Toxicity					
Component Tested Oral LD ₅₀ (rat) Dermal LD ₅₀ (rabbit) Inhalation LC ₅₀ 4hr (rat)					
Glass Fiber (continuous filament) N/D N/D N/D					

N/D = Not Determined

Section 12. Ecological Information

If manufacturing by products, scraps and dust are disposed of according federal guidelines for nonregulated waste, then these materials will pose no threat to the environment. Not biodegradable.

Section 13 Disposal Considerations

RCRA: This product, if disposed as shipped, is not considered a hazardous waste as specified in 40 CFR 261. Dispose of in

accordance with all applicable federal, state and local regulations. Generation of particulates during machining and fabricating operations may be subject to Federal and State Air Pollution Control Laws.

Section 14 Transportation Information

This product, if offered for shipment, is not regulated by USDOT 49 CFR Parts 171 - 180: Regulation of Hazardous Materials				
Transportation in Commerce.				
Shipping Information	N/A			
Classification	N/A			
Identification	N/A			
Packing Group	N/A			
Label	N/A			
NOT REGULATED AS HAZMAT				

Section 15. Regulatory Information

Section 100 Hegulatory initial matter				
Regulations Governing Pr	roduct:			
Inventory Status: United States (TSCA) - All ingredients are on the inventory or exempt from listing.				
SARA TITLE III				
EPCRA 302 EHS Extremely Hazardous Substance Reporting: N/A				
EPCRA 311/312 Tier II Chemical Inventory Reporting: N/A				
Regulations Governing Ingredients				
Chemical Name	CAS #/Chemical Category	CERCLA RQ	SARA TITLE III EPCRA 313 RQ	

Section 16 Other Information

REFERENCES

CRC Press: Handbook of Chemical and Physical Constants by David R. Lide

Merck & Company: The Merck Index

Sigma-Aldrich Company: Aldrich Handbook of Fine Chemicals

Dictionary of Toxicology by Robert Lewis

US Department of Commerce, Center for Disease Control, National Library of Medicine TOXNET

US Department of Transportation, Research and Special Programs Administration: Hazardous Materials Table, Special Provisions, Hazardous Materials Communications, Emergency Response Information, and Training Requirements

The information contained herein are given in good faith but no guarantee or warranty of any kind, expressed or implied, is made with respect to the information above.

Accurate Plastics, Inc. expressly disclaims any liability which may be incurred in using the information contained herein.

Distributed by: Polymershapes Email: info@polymershapes.com

Call: 1 (866) 437-7427

Date of Issue: 5/5/2015

www.polymershapes.com