



DURAPRIME[™]

**Extra-Rugged
Extra-Protective**

**Ultra Bright White
Polystyrene Foam Board
for High-fidelity Imaging
and Substrate Contrast**

SPECIAL FEATURES

All plastic board

High-Impact Polystyrene facers with a rigid polystyrene foam core deliver excellent durability

Bright white facers that enhance digitally-printed images

Facers are pH neutral

Excellent printability

Superior bonding and cut edges resist chipping

Facers are corona treated

Available in $\frac{3}{16}$ " and $\frac{1}{2}$ " thicknesses

Durability, Versatility & Long Life

Smooth, litho-grade high-impact polystyrene liners readily accept digital printing, screen printing and vinyl lettering to create exhibits, POP displays, and signage.

Its dense, rigid, polystyrene foam core is sturdy yet lightweight.

Achieve clean cuts easily by hand or machine.

DuraPrime liners are Washable & Moisture Resistant

DuraPrime's stock colors are White or Black face with White or Black foam core. Standard sheet sizes are 48"x96" and 60"x120" in $\frac{3}{16}$ " and $\frac{1}{2}$ " thickness.

Superior Print Surface that is dent- and warp-resistant

Heavy-duty, all-plastic based, features a litho-grade surface suitable for high-fidelity printing making DuraPrime[™] ideal for permanent displays and signs.



EnCore [®] DuraPrime [™] Specifications						
Item Number	Case UPC	Sheet Size (inches)	Sheets Per Case	Sq. Feet Per Sheet	Sq. Feet Per Case	Cases Per Pallet
White DuraPrime 3/16" thickness						
960-800	50079946053963	48 x 96	16	32.00	512.00	11
960-801	50079946053970	60 x 120	16	50.00	800.00	11
White DuraPrime 1/2" thickness						
960-820	50079946054007	48 x 96	12	32.00	384.00	13
Black DuraPrime 3/16" thickness						
960-810	50079946053987	48 x 96	16	32.00	512.00	11
Black DuraPrime 1/2" thickness						
960-830	50079946054021	48 x 96	12	32.00	384.00	13
White-Black-Black DuraPrime 3/16" thickness						
960-840	50079946054045	48 x 96	16	32.00	512.00	11

Applications	
Digital Imaging	X
Exhibits	X
Framing	
Roller Laminating	X
Litho Mounting	X
Painting	X
Air Brushing	X
POP Displays	X
Screen Printing	X
Signs	X
Vinyl Lettering	X
Models	X

Fabrication Techniques	
Hand Cutting	X
Die Cutting	X
Embossing	
Scoring	X
Machine Cutting	X
Routing	X



Distributed by:



Call: 1 (866) 437-7427
Email: info@polymershapes.com
www.polymershapes.com

HANDLING SUGGESTIONS

EnCore[®] recommends using white, cotton gloves to handle DuraPrime[™] and rubbing the surface lightly with rubbing alcohol or a tack cloth to remove any debris before printing.

WARNING: EnCore[®] Foam Board is flammable and may constitute a fire hazard if improperly handled. Do not expose to an open flame or other ignition source.

Newell makes no warranty of any kind, expressed or implied, as to merchantability, fitness for a particular purpose, or any other manner with respect to DuraPrime[™]. DuraPrime is intended for interior use.