# ORABOND<sup>™</sup> 1352

# Description

This double-sided tape consists of a polyester film carrier which is layered on both sides with different adhesives. The adhesive on the covered side of the tape has excellent permanent adhesive qualities. The adhesive on the open side allows easy removal from many surfaces. The adhesive liner is coated with a double sided siliconized paper.

## Carrier

Polyester film, 1-mil

## Liner

Siliconized paper, white, 55#

# Adhesive

Covered side: rubber Open side: modified dispersion acrylate

## Area of Use

This tape is especially suitable for the installation of carpets at conferences or exhibitions (with high cohesion and easy removal). Not appropriate for porous stone or marble.

#### **Technical Data**

Thickness* (adhesive and carrier)	7.5-mil		
Temperature resistance	-40°F to +158°F		
Adhesive power*	cover side	open side	
(FINAT TM 1, on stainless steel, one side	9.14 lb/in	0.91 lb/in	after 1 min
covered with 2-mil polyester film)	9.14 lb/in 9.59 lb/in	1.14 lb/in 1.60 lb/in	after 20 min after 24 h
Shear strength*	Covered side	open side	
(FINAT TM 8, on stainless steel, one side	> 240 h	> 120 h	at 73°F
covered with 2-mil polyester film)			
Shelf life**	1 year		
Application temperature	> +64°F		
Available lengths	27-yards, 55-yards		
Available widths (in inches)	47		
	Slit rolls: 1/2, 3/4, 1, 1, 1/2, 2		

\* average \*\* in original packaging, at 68°F and 50% relative humidity

#### IMPORTANT NOTICE

All ORABOND<sup>TM</sup> products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND<sup>TM</sup> products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND™ products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

ORABOND<sup>™</sup> is a registered trademark of ORAFOL Europe GmbH.





Call: 1 (866) 437-7427 www.polymershapes.com