

FabriTac® is a removable, adhesive fabric that may be mounted to any surface and repositioned countless times. FabriTac will retain its adhesion and leaves no residue. FabriTac has a unique coating which is quick drying and water resistant. The material provides superb quality, color gamut and resolution and is compatible for use with solvent, eco-solvent, UV and Latex inks. FabriTac is designed with unique opaque properties which prevents translucency problems associated with comparable products. Available in widths from 42" - 60".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN 60001	Polyester	Polyester
Yarn dtex	DIN EN ISO 2060	166 x 166 dtex	150 x 150 denier
Adhesive	White Repositionable Adhesive		
Total Weight	ISO 534	350g/m ²	10.3 oz/yd ²
Release Film	Paper Liner 100g (Both sides PE)		
Flame Resistance	ASTME 84 Class A, NFPA 286		
Storage Recommendations	<ul style="list-style-type: none"> •All Ultraflex materials should be stored in their original packaging. •FabriTac should be stored in temperatures between 10° and 20° Celsius, and a relative humidity of 20% - 60%. 		

Applications

	Outdoor Advertising	Banner	Floor Decals	Posters	Stickers	Wall Graphics	POP/POS
Applications	■	■	■	■	■	■	■

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	* ■			

*Certified for HP Latex Inks

Available Sizes

Metric (m)	English (inches)
1.067, 1.37, 1.52	42, 54, 60

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)